



DRG-Cladseal EPDM stripe

Rubber sealant tape



The seal strip has a textured surface on both sides for optimum adhesion. The strip is available in 1.2 mm thickness, according to DIN 18195-2, approved as protection against rising damp.

Field of application: Waterproof and air tight insulation of building joints in the outside area
 • usable on many grounds, as: PVC, aluminium, steel, galvanized steel, glass, acrylic glass, concrete, lightweight concrete, lead, wood, asphalt, EPDM, butyl...

Advantages: does not absorb water; Water has no effect on the material • high temperature resistance • chemically stable, uncomplicated in contact with other materials • includes no diluents or additives, recyclable

Technical Information – Product characteristic

Composition	--	EPDM rubber, black
Thickness	--	0,75/1,0/1,2 mm
Roll width	--	40 – 1.1700
Roll length	--	25 m
sd-value	--	24 m/32 m/38 m
Resistance to aging	--	> 50 years
UV- resistance	--	fully and permanently
Elasticity	--	300%/100% multidimensional
Fire performance	--	E

STORAGE: AT ABOUT 5°C TO 35°C AND DRY IN ORIGINAL PACKING

Guidelines for use

The Cladseal EPDM stripe is attached to the underground with the adhesive paste 3300. The underground must be dry, stable and oil-free. Changes in the position are possible until the adhesive paste is hardened. At porous or dirty undergrounds the primer 9900 is recommended.