



DRG window film VARIO



DRG outdoor window connecting film VARIO is used to seal the window connection joint. Due to the variable Sd-value, this film is suitable for indoor and outdoor use.
Fields of application: indoor and outdoor sealing for windows and doors.

Technical data - Product features

Colour	--	black and white
Weight	DIN 53854	155 g/m²
Thickness	DIN 53855	0,48 mm
Water vapour permeability, SD value variable	--	23°C and 25,0% rel. Air humidity, SD-value [m] 20 m 23°C and 37,5% rel. Air humidity, SD-value [m] 11 m 23°C and 50,0% rel. Air humidity, SD-value [m] 11 m 23°C and 80,0% rel. Air humidity, SD-value [m] 0,32 m 23°C and 90,0% rel. Air humidity, SD-value [m] 0,16 m
Building material class/ fire behaviour	DIN 4102	B2
Temperature stability	--	-40 °C to +80 °C
Application temperature	--	-5 °C to + 40 °C
Elongation at break	EN 12311-1	Lengthwise: 34% transverse: 216%
Tear strength	EN 12311-1	Lengthwise: 549 (N/5 cm) transverse: 148 (N/5 cm)
Outdoor weathering (UV)	--	3 months white 12 months black

**STORAGE: DRY AT ROOM TEMPERATURE IN THE ORIGINAL PACKAGING;
SHELF LIFE 1 YEAR AFTER RECEIPT BY THE CUSTOMER.**

Our information in this data sheet is based on the results of practical experience and the tests carried out by us and are not warranted characteristics as defined by the BGH case law.
As we have no influence on the variety of materials or their processing Einfluss, no liability can be derived from this information or from the use of our technical consulting service. We definitely recommend that you carry out your own tests.

Please take note of our processing instructions!