




## DRG outdoor window connecting films



DRG outdoor window connecting film consists of a plasterable non-woven composite laminated on one side or alternately with butyl or self-adhesive. The outdoor connection film is used for quick and safe external, driving rain-proof and diffusion-open sealing of window connection joints and is used as a plasterable external seal.

The holding surfaces must be dry, free of oil, grease, dust and other anti-adhesive components. On very porous surfaces we recommend a primer coat of butyl & bitumen primer when bonding with butyl.

Available in different versions!

### Technical data - Product features

Material	--	Polypropylene-nonwoven composite on one side, white and black
Finished weight	g / m <sup>2</sup>	150 ± 10 %
Fire class E	--	complied
Water pressure resistance	cmVS	> 200
Adhesiveness	--	12 N/25 mm of self-adhesive
Maximum tensile force (longitudinal)	N / 5 cm	560 ± 20 %
Maximum tensile force (transverse)	N / 5 cm	100 ± 20 %
sd value	m	0,17 ± 0,05
Temperature stability	--	- 40 °C to +80 °C
Application temperature	--	- 5 °C to + 40 °C
Outdoor weathering (UV)	--	3 months 12 months

STORAGE: DRY AT ROOM TEMPERATURE IN THE ORIGINAL PACKAGING;  
SHELF LIFE 1 YEAR AFTER RECEIPT BY THE CUSTOMER.